



## Free Space Isolator (FSI Series)

The Free Space Isolator series is designed for integration within laser diode package to prevent back reflection. The high isolation, low insertion loss and large aperture features make it flexible to fit with different diode laser packaging requirements.


### Specifications

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength ( $\lambda_c$ )	nm	1064	
Peak Isolation	dB	40	52
Min. Isolation over $\lambda_c \pm 10\text{nm}$ at 23°C	dB	32	42
Typ. Insertion Loss at 23°C	dB	1.1	2.1
Max. Insertion Loss at 23°C	dB	1.2	2.3
Clear Aperture	mm	0.9	
Max. Optical Power (MFD 0.5mm)	mW	300	
Polarization Plane of Input		As Indicated	
Tilt Angle of Input Polarization	deg	0 or Specify	
Operating Temperature	°C	0 to +50	
Storage Temperature	°C	-40 to +85	

### Reliability Test Specifications

High Temperature Storage Test	85°C for 500 hours
Low Temperature Storage Test	-40°C for 500hours
High Temperature Test	230°C for 3 minutes
Temperature Cycling Test	-40°C to 85 °C, rate 2°C, dwell time at extremes for 20 minutes,500 cycles
Vibration Test	10-2000Hz sinusoidal, 20g acceleration, 3 axes
Impact Test	8 drops per axis, 1.8 meters high

### Package Dimensions



Single Stage dia2.5xL2.0mm

Dual Stage dia2.5xL3.0mm

### Ordering Information

**FSI-①-②②-③-④**

①: Stage

1 - Single Stage

2 - Dual Stage

②②: Wavelength

06 - 1064nm

SS - Specify

③: Grade

A- A grade

S - Specify

④: Package Size

1 - dia2.5mm

S - Specify