



1U SLIDE patch panel 19"

The new design of 1U fiber optic patchpanel allows you easy to install and maintain your fiber optic connections. A high density, 19 inches construction with a slide panel provides very accessible termination and maintenance without removing the panel from the rack.

Rackmount patchpanel enclosures are designed for direct termination of up to 48 fibers (24xSC DUPLEX). The heavy-duty metal body provides excellent protection for the inside fibers. A large variety of connector adapters are offered to meet your specific requirements. The LX-LP enclosures has slide and removable drawer. Can be provided fully loaded with adaptors, pigtails, cable glands or unloaded. For splicing applications, up to four splice trays can be easily mounted in side.



Dimensions

- 1U x 19" x 22cm

Features

- 19" rackmount module
- for singlemode and multimode fibers
- up to 24 adapters
- easy access to jumpers and terminated cables
- up to 4 splice cassettes
- RAL 7035 (gray) or RAL 9005 (black) powder painting as a standard
- provides minimum bending radius (1,5 ')
- available with pigtail assemblies
- adjustable mounting brackets (19" mounting posts and recessed)
- FTTH, Telecom, WDM and LAN solutions

Versions

- PP-1U-SLIDE-12SCSX - 12 ports SC simplex/E2000 simplex
- PP-1U-SLIDE-12SCDX - 12 ports SC duplex
- PP-1U-SLIDE-24SCSX - 24portów SC simplex/E2000 simplex
- PP-1U-SLIDE-24SCDX - 24portów SC duplex
- PP-1U-SLIDE-12STFC - 12 ports ST/FC
- PP-1U-SPIDE-24STFC - 24ports ST/FC