

# OMC-W36



CONNECTOR HEAT OVEN  
FOR MASS PRODUCTION

# OMC-W36

## Connector Heat Oven for Mass Production

### Features

- easily programmable by user
- simple operation by single push of a button
- detachable ferrule cassette with replaceable groove plate for various cord diameters
- high capacity (42 ferrules 1.25 mm, 36 ferrules 2.5mm or 18 standard SC, FC, ST, FSMA plugs)
- adjustable and very stable cord holder
- heating plate and ferrule holder are made of copper for fast heat transfer and quick cure
- wide temperature range up to 200°C
- CE marking available

### Specifications

- operating temperature range: 40°C - 200°C (104°F - 392°F)
- stable cure temperature: +/- 2°C
- power supply: AC 100/110/230V, 50/60Hz (factory setting)
- power consumption: 250W
- dimension: 420(W) x 230(D) x 130(H) mm
- weight: 7kg

### Ordering information

OMC - W36 - X - XX - XX XX

#### Power supply

- 1 - AC 100/110 V
- 2 - AC 230V

#### Cassette for ferrules/plugs

- 01 - cassette for 36 ferrules 2.5 mm
  - 02 - cassette for 42 ferrules 1.25 mm
  - 03 - cassette for 18 SC, FC, ST plug type connectors
  - 04 - cassette for 30 LC/MU plug type connectors
  - 05 - cassette for 18 FSMA 905 plug type connector
- Custom made cassettes available!

#### Groove plate option

- 09 36 - groove plate for 36 x 0.9 mm cords
  - 09 42 - groove plate for 42 x 0.9 mm cords
  - 09 18 - groove plate for 18 x 0.9 mm cords
  - 09 30 - groove plate for 30 x 0.9 mm cords
  - 20 36 - groove plate for 32 x 2 mm cords
  - 20 42 - groove plate for 42 x 2 mm cords
  - 20 18 - groove plate for 18 x 2 mm cords
  - 20 30 - groove plate for 30 x 2 mm cords
  - 30 36 - groove plate for 36 x 3 mm cords
  - 30 18 - groove plate for 18 x 3 mm cords
- Custom made groove plates available!



Address: OptoCon Slovakia s.r.o.,  
Strojnicka 29,  
821 05 Bratislava,  
Slovak republic

Phone: +421 2 48205 200  
Fax.: +421 2 48205 231  
Email: [optocon@optocon.sk](mailto:optocon@optocon.sk)  
Web: [www.optocon.sk](http://www.optocon.sk)