



## SingleMode Fiber Coupled Diode Laser System



- 405nm,635nm,650nm,670nm,685nm,785nm,830nm,850nm,880nm,1310nm,1550nm
- 1mW to 60mW Output Power
- PM fiber/SM fiber( MM fiber Optional)
- CW/TTL/Analog Modulation
- Built-in TEC Cooling
- Output power adjustable
- High power stability
- High temperature stability
- 3-Channels Laser system optioal
- 3-Wavelength Laser System Optional
- Custom-Built Wavelengths, Powers

## Single-Mode Fiber Coupled Laser System

Type No.	Specification
<b>405nm</b> Fiber coupled diode laser system	PM/SM/MM fiber
● WSLs-405-015m-4	405nm/0~15mw power adjustable/4um SM fiber/Built-in TEC Cooling
● WSLs-405-015m-PM	405nm/0~15mw power adjustable /PM fiber/ Built-in TEC Cooling
● WSLs-405-045m-4	405nm/0~45mw power adjustable/4um SM fiber/ Built-in TEC Cooling
● WSLs-405-055m-PM	405nm/0~55mw power adjustable /PM fiber/ Built-in TEC Cooling
<b>Custom-built 405nm Fiber coupled Diode Laser System</b>	
● with SM/PM/MM Fiber	





- CW / TTL Modulation

### 635nm Fiber coupled diode laser system      PM/SM/MM fiber

● WSL-635-005m-PM	635nm/0~5mw power adjustable/PM fiber/ Built-in TEC Cooling
● WSL-635-005m-4	635nm/0~5mw power adjustable/4um SM fiber/ Built-in TEC Cooling

### Custom-built 635nm Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation

### 650nm Fiber coupled diode laser system      PM/SM/MM fiber

● WSL-650-030m-4	650nm/0~30mw power adjustable/4um SM fiber/ Built-in TEC Cooling
● WSL-650-030m-PM	650nm/0~30mw power adjustable/PM fiber/ Built-in TEC Cooling

### Custom-built 650nm Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation

### 670nm Fiber coupled diode laser system      PM/SM/MM fiber

● WSL-670-001m-4	670nm/0~1mw power adjustable/4um SM fiber/ Built-in TEC Cooling
● WSL-670-001m-PM	670nm/0~1mw power adjustable/PM fiber/ Built-in TEC Cooling

### 685nm Fiber coupled diode laser system      PM/SM/MM fiber

● WSL-685-009m-4	685nm/0~9mw power adjustable/4um SM fiber/ Built-in TEC Cooling
● WSL-685-009m-PM	685nm/0~9mw power adjustable/PM fiber/ Built-in TEC Cooling

### Custom-built 685nm Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation

### 785nm Fiber coupled diode laser system      PM/SM/MM fiber

● WSL-785-030m-4	785nm/0~30mw power adjustable /4um SM fiber/ Built-in TEC Cooling
● WSL-785-030m-PM	785nm/0~30mw power adjustable /PM fiber/ Built-in TEC Cooling





## Custom-built 785nm Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation

### 830nm Fiber coupled diode laser system      PM/SM/MM fiber

- WLSL-830-014m-4      830nm/0~14mw power adjustable /4um SM fiber/ Built-in TEC Cooling
- WLSL-830-014m-PM      830nm/0~14mw power adjustable /PM fiber/ Built-in TEC Cooling

## Custom-built 830nm Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation

### 850nm Fiber coupled diode laser system      PM/SM/MM fiber

- WLSL-850-014m-4      850nm/0~14mw power adjustable /4um SM fiber/ Built-in TEC Cooling
- WLSL-850-014m-PM      850nm/0~14mw power adjustable /PM fiber/ Built-in TEC Cooling

## Custom-built 850nm Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation

### 880nm Fiber coupled diode laser system      PM/SM/MM fiber

- WLSL-880-002m-PM      880nm/0~2mw power adjustable/ PM fiber / Built-in TEC Cooling
- WLSL-880-002m-4      880nm/0~2mw power adjustable/4um SM fiber/ Built-in TEC Cooling

### 1310nm Fiber coupled diode laser system      PM/SM fiber

- WLSL-1310-005m-9-DFB      1310nm/DFB/0~5mw power adjustable /9um SM fiber/ TEC Cooling

## Custom-built 1310nm Fiber coupled Diode Laser System

- with SM(4um,9um)/PM Fiber
- CW / TTL Modulation

### 1550nm Fiber coupled diode laser system      PM/SM fiber

- WLSL-1550-003m-9-DFB      1550nm/DFB/0~3mw power adjustable /9um SM fiber/ TEC Cooling



## Custom-built 1550nm Fiber coupled Diode Laser System

- with SM(4um,9um)/PM Fiber
- CW / TTL Modulation

## 3-Channels SM Fiber Coupled Laser System



Type No.

Specification

675nm 3-Channels Fiber Coupled Laser System

PM/SM/MM fiber

● WSLs-675-3C-001m-4

675nm/0~1mw power adjustable/4um SM fiber/Built-in TEC Cooling/  
3-Channels Output Power/High Stability

## Custom-built 3-Channels Fiber coupled Diode Laser System

- with SM/PM/MM Fiber
- CW / TTL Modulation
- Custom-built Wavelength/Power/Channel

Type No.

Specification

405nm-635nm-650nm

3-Wavelength Fiber Coupled Laser System

PM/SM/MM fiber

● WSLs-A-3C-010m-4

405nm,635nm,650nm 3Wavelength/0~10mw powe/4um SM fiber/  
Built-in TEC Cooling/3-Channels Output Power/High Stability

## Custom-built 3-Wavelength Fiber coupled Diode Laser System



# Catalog 2010



- with SM/PM/MM Fiber
- CW / TTL Modulation
- Custom-built Wavelength/Power/Channel

Wavespectrum Laser, Inc.  
[www.wavespectrum-laser.com](http://www.wavespectrum-laser.com)  
[wavespectrumlaser@gmail.com](mailto:wavespectrumlaser@gmail.com)

