

1310/1550 Single Mode Three Stage Optical Isolator

(patant pending)

Product Description

The OISM Series 1310/1550 three stage optical Isolator is a passive device that guides light at 1310/1550 nm in the normal direction while minimizing back reflection and back scattering in the reverse direction for any state of polarization. Employing Agiltron's proven advanced micro optics design, it features low insertion loss, extremely high isolation, compact structure, and high stability. These Telcordia qualified components have excellent characteristics, making them an ideal choice for application in fiber amplifier systems, pump laser diodes and optical fiber sensors.

Features

- Low Insertion Loss
- High Isolation
- Low PDL
- High Reliability
- Low Cost

Performance Specifications

OISM Dual Stage	Specification	Unit		
	1310	1310 ± 15	nm	
Operation Wavelength (λο)	C Band	1550 ± 15		
	L Band	1585 ± 15		
Typical Insertion Loss (λc, 23°C, no	≤ 0.6	dB		
Maximum Insertion Loss (Over λο, 23	≤ 0.8	dB		
Minimum Isolation (Over λο, 23°C)	≥ 55	dB		
Typical Peak Isolation (λc, 23°C)	≥ 70	dB		
Polarization Dependant Loss	≤ 0.15	dB		
Polarization Mode Dispersion	≤ 0.05	ps		
Return Loss (Minimum, Input/Outpu	≥ 55	dB		
Operating Temperature	-5 ~ +70	°C		
Storage Temperature	-40 ~ +85	°C		
Optical Power Handling	≤ 400	mW		
Package Dimensions	Ø5.5 x L40	mm		

Applications

- Optical Fiber Amplifier
- Pump Laser Source
- Fiber Optic Sensor
- Instrumentation



1310/1550 Single Mode Three Stage Optical Isolator

Ordering Information

OISM-	30							
	Туре	Wavelength	Grade	Package	Fiber Type		Fiber Length	Connector
	30=Three stage	3=1310 C=C Band L=L Band 0=Special	1=Standard 0=Special	1=Ø5.5x40 0=Special	SMF-28=1 Special=0	Bare Fiber=1 900 m Loose Tube=3 Special=0	1=0.25m 2=0.5m 3=1.0m 0=Special	1=None 2=FC/PC 3=FC/APC 4=SC/PC 5=SC/APC 6=ST/PC 7=LC 0=Special