

UltraL™ Fiber Connectors/Cables

(0.07dB assured, SM, MM)



The UltraL™ Ultra Low Loss fiber optical connectors/patch cables achieve exceptionally low coupling loss, enabling customers to design new quantum systems or lowest loss networks with higher bandwidth and longer spans. The low loss is achieved by a patent-pending automatic core alignment technology that ensures each connector has below 0.1dB loss, while ordinary connectors often have a loss of about 0.3dB. The connector uses high-quality ceramic ferrules with formats that are compatible with standard connectors and can be repolished to remove surface scratches. The ultra-low loss performance requires mating between UltraL™ connectors. Due to the near-perfect butt-mating between the two fibers, the return loss is also high, > 55dB. FC/PC is the standard connector type, while other connector types can be specially made. The UltraL™ can be cost-effectively produced in volume.

Features

- Ultra Low Loss
- High Reliability
- High Repeatability

Applications

- Quantum System
- Networks
- Data Center

Specifications

UltraL Connector SM28 Fiber	Min	Typical	Max	Unit
Operation Wavelength	1200		2000	nm
Insertion Loss	0.01	0.04	0.1	dB
NA		0.14		
Return Loss			55	dB
Operating Temperature	-40		75	°C
Storage Temperature	-45		85	°C

UltraL Connector 50/126 Fiber	Min	Typical	Max	Unit
Operation Wavelength	350		2000	nm
Insertion Loss	0.00	0.005	0.01	dB
Return Loss			40	dB
Operating Temperature	-40		75	°C
Storage Temperature	-45		85	°C

UltraL Connector SM600 Fiber	Min	Typical	Max	Unit
Operation Wavelength	1200		2000	nm
Insertion Loss	0.01	0.04	0.07	dB
NA		0.14		
Return Loss			55	dB
Operating Temperature	-40		75	°C
Storage Temperature	-45		85	°C

UltraL™ Fiber Connectors/Cables

(0.07dB assured, SM, MM)

Specifications

UltraL Connector SM450 Fiber	Min	Typical	Max	Unit
Operation Wavelength	490		633	nm
Insertion Loss		0.3	0.6	dB
NA		0.13		
Return Loss			55	dB
Operating Temperature	-40		75	°C
Storage Temperature	-45		85	°C

UltraL Connector SM400 Fiber	Min	Typical	Max	Unit
Operation Wavelength	405		532	nm
Insertion Loss		0.4	0.6	dB
NA		0.13		
Return Loss			50	dB
Operating Temperature	-40		75	°C
Storage Temperature	-45		85	°C

UltraL Connector SM300 Fiber	Min	Typical	Max	Unit
Operation Wavelength	320		430	nm
Insertion Loss		0.5	1.1	dB
NA		0.13		
Return Loss			50	dB
Operating Temperature	-40		75	°C
Storage Temperature	-45		85	°C

Ordering Information

Prefix	Fiber Type	Connector	1	1	1 1	1	Cable Type	Length
ULFC-	SM28 =1 50/125=2 60/125=3 SM600= 6 SM450 =5 SM400= 4 SM300= 3	FC/PC=1					3 mm tube=3 900um loose=2 Special=0	1m=1 2m=2 5m=5