

FuseConnect™ SC Connector

- Fusion Spliced Field Installable Connector



1. Introduction


The FuseConnect™ SC connector is part of a series of field installable connectors that employs a fusion splicer to terminate the connector in the field. It is compatible with the standard SC connector, and demonstrates performance comparable to factory built jumpers.

Connector plug unit that is equipped with pre-polished connector can be easily set on fusion splicer for fusion splice connection purpose. Fusion splice addresses return loss concerns present in analog optical networks. This advanced process yields true APC performance of return loss in SC/APC configuration.

The unique and innovative design of FUSE connect eliminates the complicated crimping operation. The simplified field installation minimizes the potential for operator error.

Compatible Fujikura’s fusion splicer models:

- FSM-60S / FSM-60R • FSM-18S / FSM-18R • FSM-50R
- FSM-17S-FH/FSM-17R • FSM-11S / FSM-11R



Simple installation process




1. Set cable and connector plug on fusion splicer and splice.



2. Slide splice sleeve over splice point.



3. Transfer to heater and heat shrink splice sleeve.




4. Assemble boot assembly and cut yam.

2. Applications


- Connectorization in:
 - RF-overlay FTTP networks
 - Cable TV backbone network
 - Outside plant
 - FTTHdesk
 - MDU FTTP Cabling
- Central office connector replacement
- Data center installation

3. Structure

3.1. FuseConnect™ SC for $\phi 2\text{mm}$ and $\phi 3\text{mm}$ cables



3.2. FuseConnect™ SC for $\phi 900\mu\text{m}$ fibers



4. Specifications

Parameter	Value
Connector type	SC [IEC61754-4]
Cable type	900μm, 2mm, 3mm
Polish	APC, UPC, PC
Insertion loss	Single-mode: Average 0.15dB, Maximum 0.40dB Multimode: Average 0.10dB, Maximum 0.30dB
Return loss	Single-mode (APC): Minimum 60dB Single-mode (UPC): Minimum 50dB Multimode : Minimum 30dB
Operating temperature	-20°C to +75°C
Environmental/mechanical characteristics	IEC 61753-1 category C

5. Performance Characteristics

Test items	Test conditions	Connector loss	Return loss
High temperature test	85 deg C, 96 hours	Max increase during and after test : 0.2dB	APC: Min 60dB UPC: Min 45dB
Low temperature test	-10 deg C, 96 hours		
Dump heat test	40 deg C, 95 %RH, 96hours		
Temperature cycle test	-10 to 60 deg C, 5 cycle		
Vibration test	0.75mm, 10 - 55 Hz, 15cycle 1 octave / min , 3 axes		
Flex test	2N, 100 cycle , ±90°		
Cable retention	900um 5N , 60s		
	2mm/3mm 50N , 120s		
Impact test	5 drops from 1.5m height		
Tensile strength of coupling mechanism	40N , 60s		
Mating durability	500 times		

6. Tool information



Jacket Stripper



Yarn Cutter



φ 0.9Fiber Stripper



Jacket Splitter



Cable Clamp

7. Ordering information

① ②

FuseConnect-SC-SF-□□-□□

① Fiber type

- **APC** : Single-mode; APC polished
- **SM** : Single-mode; UPC polished
- **GI5** : Multimode 50μm; PC polished
- **GI6** : Multimode 62.5μm; PC polished
- **10G** : Multimode 50μm; PC polished

② Cable type

- **09** : φ900μm
- **20/30** : φ2mm and φ3mm

8. Package Information:

10pcs / 1 package

9. References

IEC 61754-4

IEC 61753-1 category C

Fujikura Ltd.

<http://www.fujikura.co.jp/>

1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan

Tel: +81(3)5606-1206 Fax: +81(3)5606-1536

Important Notice

Fujikura does not accept responsibility or liability, direct or consequential arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict Fujikura's liability for death or personal injury arising from its negligence. All questions of liability relating to Fujikura products are governed by the seller's terms of sale subject where applicable to the prevailing law. If any goods supplied or processed by or on behalf of Fujikura prove on inspection to be defective in material or workmanship, Fujikura will (at its option) replace the same or refund to the buyer the price of the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.

Specifications are subjected to change without notice.