

3x3 Fused PM Fiber Standard Splitter

Features	
Low excess loss & low IL High Extinction Ratio High Reliability and Stability	
Application	
Optical Sensor Optical Amplifier Optical Testing Equipment	

Specifications

Type Parameter	3x3	
Operating wavelength (nm)	1310, 1550,	
Operating bandwidth (nm)	±15	
Grade	P	A
Excess loss (dB)	0.8	1.0
Insertion loss (dB)	≤5.8	≤6.0
Extinction Ratio(dB)	≥17	≥15
Directivity (dB)	≥50	
Operating temperature (°C)	-40 ~ +85	

Package Information

Configuration	3x3	
Fiber length	0.8, others on request	
Fiber Type	Panda Fiber	
Pigtail type	250μm bare fiber	900μm loose tube
Dimensions(mm)	φ3.0×54	Φ4X70

Ordering Information

CP	Type	Grade	Port Type	Wavelength (nm)	Coupling Ratio	Pigtail Type	Fiber Type	Length	Connector	Package
	PS=PM Fused coupler	P A	3x3	1310 1550	EVEN	0=250um bare fiber 1=900um loose tube	5=Panda fiber1	0.8=0.8m	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC XX=Others	3x54 4x70