







List of Available Cable Management






For single fiber (Magnetic type)

Cable Management P/N	Cable O.D	Method	Corresponding Polishing Holder P/N	External Image
IPC-P-CMH-SCA18	2 to 7mm	Clip-clamp	PH55-CP8C-18 PH55-CP8A-18	
IPC-P-CMH-SCA18-W	2 to 7mm	Double Clip-clamp	PH55-CP8C-18 PH55-CP8A-18 NOTE 1) For OptiTap use, this is the suitable type. 2) Also use of the Removable housing is necessary. 3) Polishing shall be done before crimp	
IPC-P-CMH-LC32DHP	2 to 7mm	Clip-clamp	PH55-PL-32DHP PH55-PL-32DFX (Single and Uniboot use)	
IPC-P-CMH-LC24	2 to 7mm	Clip-clamp	PH55-PL-24 (Single boot use)	Same construction as the above IPC-P-CMH-LC32DHP but has 12 clips instead of 16 clips



For single fiber (Magnetic type)

Cable Management P/N	Cable O.D	Method	Corresponding Polishing Holder P/N	External Image
IPC-P-CMH-SCA32	2 to 4mm	Holding groove	PH55-CP8C-32 PH55-CP8A-32	
IPC-P-CMH-SCA32-D5	5 to 6 mm	Holding groove	PH55-CP8C-32 PH55-CP8A-32	Same construction as the above IPC-P-CMH-SCA32. Cable holding groove width is wider to accept larger OD cables
IPC-P-CMH-LC48DHP-U	2 to 3mm	Holding groove	PH55-PL-48DHP (Uniboot use)	
IPC-P-CMH-LC48HP-U	2 to 3mm	Holding groove	PH55-PL-48 (Uniboot use)	Same set up as the above IPC-P-CMH-LC48DHP-U. Pitch of the cable holding grooves is optimized for PH55-PL-48
IPC-P-CMH-LC48	2 to 3mm	Holding groove	PH55-PL-48 (Single boot use)	Same set up as the above IPC-P-CMH-LC48DHP-U. Qty of cable holding groove is different (X2) for single boot use.
IPC-P-CMH-LA48	2 to 3mm	Holding groove	PH55-PL8A-48 PH55-PL8A-48HP	

For single fiber (Bolt-in type)

Cable Management P/N	Cable O.D	Method	Corresponding Polishing Holder P/N	External Image
IPC-P-CMH-LCA32-U	2 to 7mm	Clip-clamp	PH55-PL8A-32DHP-POR PH55-PL8A-32DFX-POR *1 (Uniboot use *2) NOTE *1: Use with SFP-560A only * 2: Uniboot must be SG	
FXH-P-CMH-LC32-U	2 to 4mm	Clip-clamp	PH55-PL-32DFX *1 (Uniboot use) NOTE *1: Use with SFP-560A only	
FXH-P-CMH-LC48-U	2 to 4mm	Clip-clamp	PH55-PL-48DFX *1 (Uniboot use) NOTE *1: Use with SFP-560A only	

For Multi Fiber (Bolt-in type)

Cable Management P/N	Cable O.D	Method	Corresponding Polishing Holder P/N	External Image
MT-P-CMH56-B	4 to 8mm	Screw lock	<u>NOTE: USE WITH SFP-560A ONLY</u> PH55-MT-12S1 PH55-MT8A-12S1 PH55-MT-24S1 PH55-MT8A-24S1 PH55-MT-12SQ1-B PH55-MT-24SQ1-B PH55-MT8A-12SQ1-B PH55-MT8A-24SQ1-B	
MT-P-CMH56-D (STANDARD)	2 to 4mm	Spring lock	<u>NOTE: USE WITH SFP-560A ONLY</u> PH55-MT-12S1 PH55-MT8A-12S1 PH55-MT-24S1 PH55-MT8A-24S1 PH55-MT-12SQ1-B PH55-MT-24SQ1-B PH55-MT8A-12SQ1-B PH55-MT8A-24SQ1-B	
MT-P-CMH56-E	5 to 13mm	Screw lock	<u>NOTE: USE WITH SFP-560A ONLY</u> PH55-MT-12S1 PH55-MT8A-12S1 PH55-MT-24S1 PH55-MT8A-24S1 PH55-MT-12SQ1-B PH55-MT-24SQ1-B PH55-MT8A-12SQ1-B PH55-MT8A-24SQ1-B (12 cables only)	